

CEILING SURFACE MOUNTED LIGHT

Technical Data

Application Category	Ceiling Surface Mounted Light
Wattage	10W
Lumen	1000lm
Ingress Protection	IP65
Material	Die-cast aluminum housing, Clear/opal tempered glass diffuser
Coatings	Outdoor grade anti-corrosion polyester powder coating
Light Source	CREE / OSRAM
Life Span	70% luminous flux maintained over 5000 hours
Screws	Stainless Steel
Power Supply	AC100~240V
Gasket	Rubber
Glass	Clear/opal tempered glass
Cable Gland	Stainless steel cable gland
Power Cable	30cm rubber power cable
Dimension	250*110*100mm
Net Weight	N/A



Features

Reliable structure design, high lumen maintenance 50,000 hours (L70 at 25°C).
Outdoor grade anti-corrosion powdercoating on fixture surface, suitable for extreme environment condition.

Family	Type	Led Chips	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
Ceiling Surface Mounted Light	CML	CREE Osram	10- 10W	80 - 80 CRI	15 Deg	27- 2700K	Matt Black Graphite Grey	AC100~240V	-
				90 - 90 CRI	30 Deg	30- 3000K			
				(On request)	45 Deg	40- 4000K			
					60 Deg	60- 6000K			

