


Technical Data

Application Category	Strip Lights.
Wattage	4.8w, 9.6w, 14.4w
Source Lumen	540lm, 1080lm, 1620lm
Ingress Protection	IP67
IK Rating	IK08
Material	Double Sided High Copper Flexible PCB With Heavy Outdoor Rated Silicon Casing.
Coatings	White PCB
Light Source	Low Power Led (Bridgelux)
Life Span	50000 hrs*
Screws	N/A
Power Supply	Remote 24v DC
Cutting length	50 mm
Reel size	5 meter
led qty	120 led's per mtr
Power Cable	150 mm
Dimension	12mm x 20mm



Description:

The Flex LED Strip Fulfills The Higher Demands On An Absolute Homogenous Illumination From Close Up Light Haunches. 120 Points Of Light Per Mtr. Gurantee A complete Constant Line of Light. FLEX Ssystem impresses With An Excellent Price Performance Ratio. Its Maintainance Free, Lifetime Amounts Over 50,000 Hrs As A Minimal Energy Consumption With Higher Lumen Output.

Features:

- Excellence Lumen Output<110 Lumens Per Watt.
- Uniform Colour Coordinates.
- High Quality Mechadem 3, single bin Led's
- Bridgelux international LED'S, Can be supplied in CREE & OSRAM LED on request
- Very Good Thermal Management, ensuring minimum degradation of CCT and Lumen
- lowest voltage drop upto 5 mtrs, lumen consistency for entire 5 mtrs
- Double Sided High Copper Flexible PCB.

Family	Type	Code	W / Mtr	CRI	Optics	CCT	IP	Supply	Accessories
FLEX	SLO	1220-120	5- 4.8w 10 - 9.6w 15 - 14.4w	8 - 80 CRI	O - 120 Degree	27 - 2700K 30- 3000K 40- 4000K	67 - IP67	24 - 24V DC	

Code Example :- FLEX_SLO_1220-120_5_8_O_27_67-24

Accessories



Mounting clip

Meanwell LPV 100-24(5 Mtr Reel)

Note: for alu. channel and power supply options contact RK lite