

## WALL MOUNTED UP-DOWNLIGHT

### Technical Data

<b>Application Category</b>	Wall Up-Downlight
<b>Wattage</b>	20W
<b>Lumen</b>	2000lm
<b>Ingress Protection</b>	IP65
<b>Material</b>	Die-cast aluminum housing, Clear/opal tempered glass diffuser
<b>Coatings</b>	Outdoor grade anti-corrosion polyester powder coating
<b>Light Source</b>	CREE / OSRAM
<b>Life Span</b>	70% luminous flux maintained over 5000 hours
<b>Screws</b>	Stainless Steel
<b>Power Supply</b>	AC100~240V
<b>Gasket</b>	Rubber
<b>Glass</b>	Clear/opal tempered glass
<b>Cable Gland</b>	Stainless steel cable gland
<b>Power Cable</b>	30cm rubber power cable
<b>Dimension</b>	250*110*100mm
<b>Net Weight</b>	N/A



### Features

Reliable structure design, high lumen maintenance 50,000 hours (L70 at 25°C).  
Outdoor grade anti-corrosion powdercoating on fixture surface, suitable for extreme environment condition.

Family	Type	Led Chips	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
Wall Up-Downlight	WL	CREE Osram	20- 20W	80 - 80 CRI 90 - 90 CRI (On request)	15 Deg 30 Deg 45 Deg 60 Deg	27- 2700K 30- 3000K 40- 4000K 60- 6000K	Matt Black Graphite Grey	AC100~240V	-

