



Technical Data

Application Category	Post Top	COMING SOON.
Wattage	62w	
Source Lumen	6480LM	
Ingress Protection	IP65	
Material	GI Pipe And Aluminium Parts.	
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.	
Light Source	SMD Led	
Life Span	50000 hrs*	
Screws	Stainless steel	
Power Supply	Integral 230vAC	
Gasket	N/A	
Glass	Extra Clear Impact Resistant Toughned Glass.	
Cable Gland	N/A	
Power Cable	Cable Not Included.	
Dimension	-	
Gross Weight	-	

Features

- High Efficiency Optical System.
- Extra Clear Glass To Increase Efficiency Of The Fixture.
- "Weather Protect" Outdoor Rated Powder Coating.
- "Long Life" Thermal Management.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
ANGLE	PT	40-4000mm ht.	62 - 62w	8 - 80 CRI	T1 - 148X107° T2 - 158X100° T3 - 160X130°	30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230vAC	-

Code Example :- ANGLE\_PT\_40\_62\_8\_T1\_30\_G-AC