BAMBOO


BAMBOO 2

Technical Data

Application Category	Bollard					
Wattage	16w					
Source Lumen	2520LM					
Ingress Protection	IP65					
Material	GI Pipe And Solid Aluminium Parts.					
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.					
Light Source	2 x COB LED					
Life Span	50000 hrs*					
Screws	Stainless steel					
Power Supply	Integral 230vAC, 24vDC					
Gasket	High Grade Long Lasting Silicon Gasket.					
Glass	Extra Clear Impact Resistant Toughned Glass					
Cable Gland	N/A					
Power Cable	Cable Not Included.					
Dimension	Width - 70 mm* Base - 130mm, Height - 700mm / 900mm					
Gross Weight	-					



RKLITE



Features

- · High Efficiency Optical System.
- Extra Clear Glass To Increase Efficiency Of The Fixture.
- "Weather Protect" Outdoor Rated Powder Coating.
- · "Long Life" Thermal Management.

CV Benefits

- · (24 V Low Voltage)
- Maximum Driver Distance Option. (Long Distance Remote Driver Location)
- Easy Maintenance & Common Driver For Many Fixtures.
- "Human Safe Design" Low Voltage Across Landscape.

Family	Туре	Code	Wattage	CRI	Optics	ССТ	Fixture Finish	Supply	Accessories
BAMBOO	BO	70-700mm ht. 90-900 mm ht.	16 - 8w + 8w	8 - 80 CRI	SP - 16° M - 22° MF - 38°	30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230VAC 24-24vDC	-

Code Example :- BAMBOO2_BO_70_16_8_SP_30_G_AC

Accessories

