WM-39UD









Technical Data

Application Category	Wall Mounted				
Wattage	4w				
Source Lumen	480LM			_	
Ingress Protection	IP65				
Material	Excellent Corrosion Anodized Solid Aluminium Body And Part.		0		
Coatings	"Duracoat" - Double Protection Anodising And Powder Coating.				
Light Source	2 x High Power Led				
Life Span	50000 hrs*				
Screws	Stainless steel				
Power Supply	Integral 230vAC				
Gasket	High Grade Long lasting Silicon Gasket.				
Glass	Extra Clear Impact Resistant Toughened Glass.				
Cable Gland	N/A	95	0		
Power Cable	Cable Not Included.				
Dimension	95 mm Height		<u> </u>		
Gross Weight	-		50	38	

Features

- · Solid Aluminium Body.
- · Extra Safety Impact Resistant Toughened Glass.
- · High Efficiency Optical System.
- Extra Clear Glass To Increase Efficiency Of The Fixture.
- · "Coro Safe" High Grade Anodizing.
- "Duracoat" Double Layer Body Coating To Withstand Corrosion.
- · "Weatherprotect" Outdoor Rated Powder Coating.
- · "Long Life" Thermal Management.

Family	Туре	Code	Wattage	CRI	Optics	сст	Fixture Finish	Supply	Accessories
BOXY	WM	39-UD	4 - 2w + 2w	8 - 80 CRI 9 - 90 CRI	SP - 10° M - 24° W - 40° WFL - 60°	27 - 2700K 30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230vAC	-

Code Example :- BOXY_WM_39UD_4_8_SP_27_G_AC