


# BULLET

CM-61-D3



## Technical Data

<b>Application Category</b>	Ceiling Mount
<b>Wattage</b>	8w
<b>Source Lumen</b>	720lm
<b>Ingress Protection</b>	IP65
<b>Material</b>	Excellent Corrosion Anodized Solid Aluminium Body And Part.
<b>Coatings</b>	"Duracoat" - Double Protection Anodising And Powder Coating.
<b>Light Source</b>	3 x High Power Led
<b>Life Span</b>	50000 hrs*
<b>Screws</b>	Stainless steel
<b>Power Supply</b>	Integral 230vAC/24vDC
<b>Gasket</b>	High Grade Long lasting Silicon Gasket.
<b>Glass</b>	Extra Clear Impact Resistant Toughened Glass.
<b>Cable Gland</b>	Silicon Gourmet
<b>Power Cable</b>	Cable Not Included.
<b>Dimension</b>	Dia 62mm, Height-90 mm
<b>Gross Weight</b>	-



## Features

- Solid Aluminium Body.
- Extra Safety Impact Resistant Toughened Glass.
- High Efficiency Optical System.
- Extra Clear Glass To Increase Efficiency Of The Fixture.
- "Coro Safe" High Grade Anodizing.
- "Duracoat" Double Layer Body Coating To Withstand Corrosion.
- "Weatherprotect" Outdoor Rated Powder Coating.
- "Long Life" Thermal Management.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
BULLET	CM	61-D3	8 - 8w	8 - 80 CRI 9 - 90 CRI	SP - 10° M - 24° W - 40° WFL - 60°	27 - 2700K 30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230VAC 24-24vDC	HL-48 - Hexcell Louvre

Code Example :- BULLET\_CM\_61-D3\_8\_8\_SP\_27\_G\_AC\_HL-48

## Accessories



HL-48  
(Hexcell Louvre )