



# BULLET

WM-61UD-D3



## Technical Data

<b>Application Category</b>	Wall Mounted
<b>Wattage</b>	14w
<b>Source Lumen</b>	1440LM
<b>Ingress Protection</b>	IP65
<b>Material</b>	Excellent Corrosion Anodized Solid Aluminium Body And Part.
<b>Coatings</b>	"Duracoat" - Double Protection Anodising And Powder Coating.
<b>Light Source</b>	6 x High Power Led
<b>Life Span</b>	50000 hrs*
<b>Screws</b>	Stainless steel
<b>Power Supply</b>	Integral 230vAC, 24vDC
<b>Gasket</b>	High Grade Long lasting Silicon Gasket.
<b>Glass</b>	Extra Clear Impact Resistant Toughened Glass.
<b>Cable Gland</b>	Silicon Gourmet
<b>Power Cable</b>	Cable Not Included.
<b>Dimension</b>	61 mm Dia 228 mm Height
<b>Gross Weight</b>	-



## Features

- Solid Aluminium Body.
- Extra Safety Impact Resistant Toughened Glass.
- High Efficiency Optical System.
- Extra Clear Glass To Increase Efficiency Of The Fixture.
- "Coro Safe" High Grade Anodizing.
- "Duracoat" Double Layer Body Coating To Withstand Corrosion.
- "Weatherprotect" Outdoor Rated Powder Coating.
- "Long Life" Thermal Management.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
BULLET	WM	61UD-D3	14 - 7w + 7w	8 - 80 CRI 9 - 90 CRI	SP - 10° M - 18° WFL - 54°	27 - 2700K 30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230VAC 24-24VDC	HL-48 - Hexcell Louvre

Code Example :- BULLET\_WM\_61UD-D3\_14\_8\_SP\_27\_G\_AC\_HL-48

## Accessories



HL-48  
(Hexcell Louvre )