

COLUMN

COLUMN



Technical Data

Application Category	Post Top
Wattage	60W
Source Lumen	7200lm
Ingress Protection	IP65
Material	GI Pipe And Aluminium Parts.
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.
Light Source	SMD LED
Life Span	50000 hrs*
Screws	Stainless steel
Power Supply	Integral 230vDC- Junction Box
Gasket	N/A
Diffuser	High Grade PMMA Frosted Acrylic.
Cable Gland	N/A
Power Cable	Cable Not Included.
Dimension	3000 mm Height*300 mm
Gross Weight	-




Features

- High Efficiency Optical System
- Extra Clear Glass To Increase Efficiency Of The Fixture.
- "Weather Protect" Outdoor Rated Powder Coating.
- "Long Life" Thermal Management.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
COLUMN	PT	30-3000mm ht.	60 - 60w	8 - 80 CRI	DF - Diffused	30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230vAC	-

Code Example :- COLUMN_PT_30_60_8_DF_30_G_AC

Accessories



Foundation Kit
GPSQ-300/JB4-16x300