


FOCUS

FOCUS 1



Technical Data

Application Category	Bollard
Wattage	11W
Source Lumen	1260LM
Ingress Protection	IP65
Material	GI Pipe And Solid Aluminium Parts.
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.
Light Source	1 X COB LED
Life Span	50000 hrs*
Screws	Stainless steel
Power Supply	Integral 230vAC/24vDC
Gasket	High Grade Long Lasting Silicon Gasket.
Glass	Extra Clear Toughned Glass
Cable Gland	N/A
Power Cable	Cable Not Included.
Dimension	Width - 147 mm* Base - 130mm, Height - 750 mm / 900mm
Gross Weight	-



Features

- High Efficiency Optical System.
- Extra Clear Glass To Increase Efficiency Of The Fixture.
- "Long Life" Thermal Management.

CV Benefits

- (24 V - Low Voltage)
- Maximum Driver Distance Option. (Long Distance Remote Driver Location)
- Easy Maintenance & Common Driver For Many Fixtures.
- "Human Safe Design" Low Voltage Across Landscape.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
FOCUS	BO	75-750mm ht. 90-900mm ht.	11 - 11w	8 - 80 CRI	SP - 16° M - 22° MF - 38°	30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230VAC 24-24VDC	-

Code Example :- FOCUS 1_BO_75_11_8_SP_30_G_AC

Accessories



Foundation Kit
GPR-130/JB3-8x150