

Technical Data

Application Category	Bollard
Wattage	10W
Source Lumen	1120LM
Ingress Protection	IP65
Material	Brass Pipe & Spun Brass
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.
Light Source	1 x COB LED
Life Span	50000 hrs*
Screws	N/A
Power Supply	Remote Driver, 24vDC
Gasket	N/A
Glass	Diffused Glass.
Cable Gland	N/A
Power Cable	1000 mm All Weather Neoprene Silicon Power Cable Included.
Dimension	600 mm Height
Gross Weight	-



Features

- Consistent Antique Finish.
- Heavy Duty Tampered Glass.
- No Glare Design.
- 24v Or 230/240v Operating system.
- Safe And Easy For Installation.
- Path Lights Are Perfect For Being A Long Walkway and Paths in Parks.

CV Benefits

- (24 V - Low Voltage)
- Maximum Driver Distance Option. (Long Distance Remote Driver Location)
- Easy Maintenance, Common Driver For Many Fixtures.
- "Human Safe Design" Low Voltage Across Landscape.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
FUNGO	BO	60-600mm ht.	10-10W	8 - 80 CRI	DF - Diffused	30- 3000K 40- 4000K	COPPER FINISH	Remote Driver	-

Code Example :- FUNGO_BO_60_10_8_DF_30_C