


MODELLO

MODELLO R



Technical Data

Application Category	Bollard
Wattage	11w, 15w
Source Lumen	1260LM / 1680 LM
Ingress Protection	IP65
Material	Aluminium Casting With GI Plated Pipe.
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.
Light Source	1 x COB LED
Life Span	50000 hrs*
Screws	Stainless steel
Power Supply	Integral 230vAC/24vDC
Gasket	Silicon Gasket
Glass	N/A
Cable Gland	N/A
Power Cable	Cable Not Included.
Dimension	Width - 102 mm, Height - 750mm
Gross Weight	-



Features

- Solid Aluminium Body.
- High Efficiency Optical System.
- "Long Life" Thermal Management.


CV Benefits

- (24 V - Low Voltage)
- Maximum Driver Distance Option. (Long Distance Remote Driver Location)
- Easy Maintenance & Common Driver For Many Fixtures.
- "Human Safe Design" Low Voltage Across Landscape.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
MODELLO	BO	75-750mm ht.	11 - 11w 15 - 15w	8 - 80 CRI	120 - 120° T1-110 x 160°(Elliptical) "T2-110 x 160° (Forward Through)" "T3-75 x 160° (Forward Through)"	30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230VAC 24-24VDC	-

Code Example :- MODELLO_R_75_11_8_120_30_G_AC

Accessories



Foundation Kit
GPR-106/JB2-8x150