

MODELLO

MODELLO S



Technical Data

Application Category	Bollard
Wattage	11w
Source Lumen	1260LM
Ingress Protection	IP65
Material	Aluminium Extrusion And Solid Aluminium Parts.
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.
Light Source	1 x COB LED
Life Span	50000 hrs*
Screws	Stainless steel
Power Supply	Integral 230vAC/24vDC
Gasket	N/A
Glass	N/A
Cable Gland	N/A
Power Cable	1000 mm All Weather Neoprene Silicon Power Cable Included.
Dimension	-
Gross Weight	-

COMING SOON.

Features

- Solid Aluminium Body.
- High Efficiency Optical System.
- "Long Life" Thermal Management.

CV Benefits

- (24 V - Low Voltage)
- Maximum Driver Distance Option. (Long Distance Remote Driver Location)
- Easy Maintenance, Common Driver For Many Fixtures.
- "Human Safe Design" Low Voltage Across Landscape.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
MODELLO	BO	75-750mm ht.	11 - 11w	8 - 80 CRI	120 - 120° T1-110 x 160°(Elliptical) "T2-110 x 160° (Forward Through)" "T3-75 x 160° (Forward Through)"	30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230VAC 24-24vDC	-

Code Example :- [MODELLO_S_75_11_8_120_30_G_AC](#)