

Technical Data

Application Category	Post Top
Wattage	80W
Source Lumen	9600lm
Ingress Protection	IP65
Material	GI Pipe Die Cast Aluminium And Polycarbonate.
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.
Light Source	SMD LED
Life Span	50000 hrs*
Screws	Stainless steel
Power Supply	Integral 230vAC
Gasket	SiliconGasket
Diffuser	Polycarbonate Diffuser
Cable Gland	N/A
Power Cable	Cable Not Included.
Dimension	Width - 172 mm* Base - 300mm, Height - 3000mm
Gross Weight	-




Features

- High Efficiency Optical System
- High Grade Polycarbonate Diffuser.
- "Weather Protect" Outdoor Rated Powder Coating.
- "Long Life" Thermal Management.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
PILLAR	PT	30-3000mm ht.	80 - 80w	8 - 80 CRI	DF - Diffused	30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230vAC	-

Code Example :- PILLAR_PL_30_80_8_DF_30_G-AC

Accessories



Foundation Kit
GPR-300/JB4-16x300