

Technical Data

Application Category	Post Top
Wattage	45w
Source Lumen	4703LM
Ingress Protection	IP65
Material	GI Pipe And Aluminium Parts.
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.
Light Source	SMD LED
Life Span	50000 hrs*
Screws	Stainless steel
Power Supply	Integral 230V
Gasket	N/A
Glass	Extra Clear Impact Resistant Toughned Glass.
Cable Gland	N/A
Power Cable	Cable Not Included.
Dimension	875mm*4000 mm Height*300 mm
Gross Weight	-




Features

- High Efficiency Optical System
- Clear Glass To Increase Efficiency Of The Fixture.
- "Weather Protect" Outdoor Rated Powder Coating.
- "Long Life" Thermal Management.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
SETTE	PT	40-4000mm ht.	62 - 62w	8 - 80 CRI	T1 - 148X107° T2 - 158X100° T3 - 160X130°	30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230vAC	-

Code Example :- SETTE_PT_40_62_8_T1_30_G-AC

Accessories



Foundation Kit
GPSQ-300/JB4-16x300