





Technical Data

Application Category	Bollard
Wattage	10W
Source Lumen	1080LM
Ingress Protection	IP65
Material	Aluminium Extrusion and Aluminium Parts.
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.
Light Source	1 x COB LED
Life Span	50000 hrs*
Screws	StainlessSteel
Power Supply	Integral 230vAC/24vDC
Gasket	High Grade Long lasting Silicon Gasket.
Glass	Clear Glass.
Cable Gland	N/A
Power Cable	Cable Not Included.
Dimension	Width - 140 mm* Base - 100mm, Height - 350 mm / 600mm
Gross Weight	-



Features

- Solid Aluminium Body.
- High Efficiency Optical System.
- "Weatherprotect" Outdoor Rated Powder Coating.
- "Long Life" Thermal Management.

CV Benefits

- (24 V - Low Voltage)
- Maximum Driver Distance Option. (Long Distance Remote Driver Location)
- Easy Maintenance & Common Driver For Many Fixtures.
- "Human Safe Design" Low Voltage Across Landscape.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
SOLE	BO	35-350mm ht. 60-600mm ht.	10-10W	8 - 80 CRI	P-Pattern	30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230vAC 24 - 24vDC	-

Code Example :- SOLE_BO_35_10_8_P_30_G_AC

Accessories



Foundation Kit
GPSQ-92/JB2-8x150