

POST TOP LIGHT

Technical Data

| | |
|-----------------------------|---|
| Application Category | Post Top Light |
| Wattage | 60W |
| Lumen | 5800lm |
| Ingress Protection | IP65 |
| Material | Die-cast Aluminum housing Spinning Aluminum cover |
| Coatings | UV-proof powder coating |
| Light Source | Lumileds LED |
| Life Span | 50000 Hrs |
| Screws | Stainless Steel |
| Power Supply | 100-240V 50-60Hz |
| Gasket | Silicone rubber |
| Glass | Clear PC diffuser |
| Cable Gland | N/A |
| Power Cable | N/A |
| Dimension | Φ370*H530mm |
| Net Weight | N/A |



Features

- Material: Die-cast Aluminum housing Spinning Aluminum cover
- Electronic transformer 100-240V 50/60Hz included.
- Stainless steel screws.
- Silicone rubber gasket.
- Clear PC diffuser.
- Garden, Round shape fixture, for outdoor surface installation.

| Family | Type | Led Chips | Wattage | CRI | Optics | CCT | Fixture Finish | Supply | Accessories |
|----------------|------|-----------|---------|-----------|--------|-------------------------------------|----------------|------------|-------------|
| Post Top Light | PTL | Lumileds | 60- 60W | 8- 80 CRI | N/A | 30- 3000K 40- 4000K 60- 6000K | N/A | AC100-240V | - |

