


## Technical Data

Application Category	Spot Light
Wattage	2w
Source Lumen	180lm
Ingress Protection	IP66
Material	Excellent Corrosion Anodized Solid Aluminium Body And Part.
Coatings	"Duracoat" - Double Protection , Anodising And Powder Coating.
Light Source	1 x High Power Led
Life Span	50000 hrs.*
Screws	Stainless steel
Power Supply	Remote CC Driver (3V, 700mA)
Gasket	High Grade Long Lasting Silicon Gasket.
Glass	Extra Clear Impact Resistant Toughened Glass.
Cable Gland	Double Nickel-Plated German Brass Cable Gland M12,High Quality Silicon Gourmet.
Power Cable	1000 mm All Weather Neoprene Silicon Power Cable Included.
Dimension	32 mm Dia 93 mm Height.
Gross Weight	-




## Features

- Solid Aluminium Body.
- Extra Safety Impact Resistant Toughened Glass.
- High Efficiency Optical System.
- Extra Clear Glass To Increase Efficiency Of The Fixture.
- High Grade Brass Nickel Plated German Gland.
- High Grade Neoprene Silicon Based Italian Cable To Withstand Any Weather Conditions .
- Recessed Spike Made Of GFR Polymer.
- "Coro Safe" High Grade Anodizing.
- "Duracoat" Double Layer Body Coating To Withstand Corrosion.
- "Weather Protect" Outdoor Rated Powder Coating.
- "Capillary Protect System" Anti-Capillary System To Protect Any Water Ingress From Cable Joints.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
Cielo	SP	32	2 - 2w	8 - 80 CRI 9 - 90 CRI (On request*)	SP - 10° M - 24° W - 40° WFL - 60° EL- 30x 65°	27 - 2700K 30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	CC - Constant Current Driver	HL-20- Hexcell Louvre

Code Example :- CIELO\_SP\_32\_1.5\_8\_SP\_27\_G\_CC\_HL-20

## Accessories

HL-20  
(Hexcell Louvre )Tree Belt  
TB-30-1.5

SP32-COWL



ARM-200

Meanwell APC  
8-700 , IP42