



Technical Data

Application Category	Post Top
Wattage	60w (40+20w),
Source Lumen	7140LM
Ingress Protection	IP65
Material	GI Pipe And Aluminium Parts.
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.
Light Source	SMD LED
Life Span	50000 hrs*
Screws	Stainless steel
Power Supply	Integral 230vAC
Gasket	N/A
Glass	High Grade PMMA Frosted Diffuser
Cable Gland	N/A
Power Cable	Cable Not Included.
Dimension	Width - 800mm * 4000 mm Height * 300 mm Base
Gross Weight	-




Features

- High Efficiency Optical System
- High Grade PMMA Frosted Diffuser.
- "Weather Protect" Outdoor Rated Powder Coating
- "Long Life" Thermal Management.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
CILLINDRO	PT	40-4000mm ht.	60-40W + 20W (40w Down) (20W Up)	8 - 80 CRI	120 - 120° T1-110 x 160°(Elliptical) "T2-110 x 160° (Forward Through)" "T3-75 x 160° (Forward Through)"	30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230vAC	-

Code Example :- CILLINDRO_PT_40_60_8_120_30_G-AC

Accessories



Foundation Kit
GPR-300/JB4-16x300