


Technical Data

| | |
|----------------------|---|
| Application Category | Spot Light |
| Wattage | 20w |
| Source Lumen | 2160LM |
| Ingress Protection | IP66 |
| Material | Excellent Corrosion Anodized Solid Aluminium Body And Part. |
| Coatings | "Duracoat" - Double Protection - Anodising And Powder Coating. |
| Light Source | 3 x High Power Led |
| Life Span | 50000 hrs.* |
| Screws | Stainless steel |
| Power Supply | Integral 230vAC/24vDC |
| Gasket | High Grade Long Lasting Silicon Gasket. |
| Glass | Extra Clear Impact Resistant Toughened Glass. |
| Cable Gland | Double Nickel-Plated German Brass Cable Gland M12,High Quality Silicon Gourmet. |
| Power Cable | 1000 mm All Weather Neoprene Silicon Power Cable Included. |
| Dimension | 88 mm Dia 186 mm Height. |
| Gross Weight | - |



Features

- Solid Aluminium Body.
- Extra Safety Impact Resistant Toughened Glass.
- High Efficiency Optical System.
- Extra Clear Glass To Increase Efficiency Of The Fixture.
- High Grade Brass Nickel Plated German Gland.
- High Grade Neoprene Silicon Based Italian Cable To Withstand Any Weather Conditions .
- Recessed Spike Made Of GFR Polymer.
- "Coro Safe" High Grade Anodizing.
- "Duracoat" Double Layer Body Coating To Withstand Corrosion.
- "Weather Protect" Outdoor Rated Powder Coating.
- "Capillary Protect System" Anti-Capillary System To Protect Any Water Ingress From Cable Joints.

CV Benefits

- Long Lenght Operation & Maximum Driver Distance Option.
- Easy Maintenance & Common Driver For Many Fixtures.
- "Human Safe Design" Low Voltage Across Landscape.
- "Long Life" Thermal Management.

| Family | Type | Code | Wattage | CRI | Optics | CCT | Fixture Finish | Supply | Accessories |
|--------|------|-------|----------|--------------------------|---|--------------------------------------|--|----------------------------|-----------------------|
| Lugar | SP | 88-HP | 20 - 20w | 8 - 80 CRI 9 - 90 CRI | SP - 10° M - 24° W - 40° WFL - 60° | 27 - 2700K 30- 3000K 40- 4000K | G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green | 230 - 230vAC 24 - 24vDC | HL-68- Hexcell Louvre |

Code Example :- LUGAR_SP_88-HP_20_8_SP_27_G_AC_HL-68


Accessories



HL-68
(Hexcell Louvre)



Tree Belt
TB-50-1.5



SP88-COWL



ARP-220