

Technical Data

Application Category	Post Top
Wattage	60w
Source Lumen	7560LM
Ingress Protection	IP65
Material	GI Pipe And Aluminium Parts.
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.
Light Source	SMD LED
Life Span	50000 hrs*
Screws	Stainless steel
Power Supply	Integral 230vAC
Gasket	N/A
Glass	Lens
Cable Gland	N/A
Power Cable	Cable Not Included.
Dimension	-
Gross Weight	-

COMING SOON.

Features

- High Efficiency Optical System
- Extra Clear Glass To Increase Efficiency Of The Fixture..
- "Weatherprotect" Outdoor Rated Powder Coating.
- "Long Life" Thermal Management.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
MODELLO	PT	40-4000mm ht.	60 - 60w	8 - 80 CRI	120 - 120° T1-110 x 160°(Eliptical) T2-110 x 160° (Forward Through) T3-75 x 160° (Forward Through)	30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230vAC	-

Code Example :- MODELLO\_PT\_40\_60\_8\_120\_30\_G-AC