



Technical Data

Application Category	Bollard
Wattage	18W
Source Lumen	1920LM
Ingress Protection	IP65
Material	GI Pipe And Solid Aluminium Parts.
Coatings	"Weather Protect" High Grade Pure Polyester, Outdoor Powder Coating.
Light Source	8 x High Power Led
Life Span	50000 hrs*
Screws	Stainless steel
Power Supply	Integral 230V, 24V DC
Gasket	High Grade Long Lasting Silicon Gasket.
Diffuser	High Grade PMMA frosted Diffuser.
Cable Gland	N/A
Power Cable	Cable Not Included.
Dimension	Width - 196 mm* Base - 130mm, Height - 350mm / 600mm / 900mm
Gross Weight	-



Features

- Solid Aluminium Body.
- High Efficiency Optical System.
- High Grade PMMA frosted Diffuser Increase Efficiency Of The Fixture.
- "Weatherprotect" Outdoor Rated Powder Coating.
- "Long Life" Thermal Management.

CV Benefits

- (24 V - Low Voltage)
- Maximum Driver Distance Option. (Long Distance Remote Driver Location)
- Easy Maintenance, Common Driver For Many Fixtures.
- "Human Safe Design" Low Voltage Across Landscape.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
MUSHO	BO	35-350mm ht. 60-600mm ht. 90-900mm ht.	14- 14w 18 - 18w	8 - 80 CRI	DF - Diffused	30- 3000K 40- 4000K	G-Graphite Grey B-Black W-White C - Corton G - Dark leaf Green	230 - 230V AC 24-24 VDC	-

Code Example :- MUSHO_BO_35_14_8_DF_30_G

Accessories



Foundation Kit
GPR-130/JB3-8x150