

Technical Data



Application Category	Strip Lights.
Wattage	4.8W, 9.6W, 14.4W, 19.2W,25.2w
Source Lumen	540 lm, 1080lm, 1620lm, 2160lm,3060lm
Ingress Protection	IP20
Material	Double Sided High Copper Flexible PCB.
Coatings	White PCB.
Light Source	Low Power Led (Bridgelux)
Life Span	50000 hrs*
Screws	N/A
Power Supply	Remote 24vDC
Gasket	N/A
Glass	N/A
Cable Gland	N/A
Power Cable	150 mm
Dimension	16.9mm*12.1mm



Gross Weight -

Description:

- The NASTRO LED Strip Fulfils The Higher Demands On An Absolute Homogenous Illumination
- From Close Up Light Haunches. 120 Points Of Light Per Mtr. Gurantee A complete Constant Line of Light.
- NASTRO Sysytem impresses With An Excellent Price Performance Ratio. Its Maintainance Free, Lifetime
- Amounts Over 50,000 Hrs As A Minimal Energy Consumption With Higher Lumen Output.

Features:

- CRI Upto 90.
- Uniform Colour Coordinates.
- High Quality Mechadem 3.
- Very Good Thermal Management, lowest voltage drop upto 5 mtrs.
- Double Sided High Copper Flexible PCB.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
NASTRO	SL-O	120 IP	4.8-5W 9.6-10W 14.4-15W 19.2-20W 25.2-25.2W	8 - 80 CRI 9 - 90 CRI	O - 120 Degree	27 - 2700K 30- 3000K 40- 4000K		24 - 24vDC	

Code Example :- NASTRO_SLO_120 IP_4.8_8_120_27_DC

Accessories



Standard Aluminium Channel



Deep Aluminium Channel