

Technical Data

Application Category	Strip Lights.
Wattage	4.8W, 9.6W, 14.4W, 19.2W,25.2w
Source Lumen	540 lm, 1080lm, 1620lm, 2160lm,3060lm
Ingress Protection	IP20
Material	Double Sided High Copper Flexible PCB.
Coatings	White PCB.
Light Source	Low Power Led (Bridgelux)
Life Span	50000 hrs*
Screws	N/A
Power Supply	Remote 24vDC
Gasket	N/A
Glass	N/A
Cable Gland	N/A
Power Cable	150 mm
Dimension	16.9mm*12.1mm



Gross Weight -

Description:

- The NASTRO LED Strip Fulfils The Higher Demands On An Absolute Homogenous Illumination
- From Close Up Light Haunches. 120 Points Of Light Per Mtr. Gurantee A complete Constant Line of Light.
- NASTRO Sysytem impresses With An Excellent Price Performance Ratio. Its Maintainance Free, Lifetime
- Amounts Over 50,000 Hrs As A Minimal Energy Consumption With Higher Lumen Output.

Features:

- Excellence Lumen Output<110 Lumens Per Watt.
- CRI Upto 90.
- Uniform Colour Coordinates.
- High Quality Mechadem 3.
- Very Good Thermal Management, lowest voltage drop upto 5 mtrs.
- Double Sided High Copper Flexible PCB.

Family	Type	Code	Wattage	CRI	Optics	CCT	Fixture Finish	Supply	Accessories
NASTRO	SL	120	4.8-5W	8 - 80 CRI	O - 120 Degree	27 - 2700K		24 - 24vDC	
			9.6-10W	9 - 90 CRI		30- 3000K			
			14.4-15W			40- 4000K			
			19.2-20W						
			25.2-25.2W						

Code Example :- NASTRO_SL120_4_8_8_120_27_DC

Accessories



Standard Aluminium Channel



Deep Aluminium Channel